



FEATURES

- Optical Loss/ORL Tester
- 34dB Dynamic Range W/1 Meter Dead Zone
- Touch Screen
- Video Scope with Auto Pass/Fail Option
- VFL & Power Meter Options
- Bluetooth Android Tablet Operation
- Fib-R- Map Event Analyzer
- Macro Bend and Bidirectional Analysis
- Full Auto, Construction and Expert Modes
- SM, MM, Triple, Quad & CWDM Units Available
- Instant On, Immediate Scan
- Live Fiber Detection
- Onboard Memory of ~40,000 traces
- CW/Fiber Identifier Light Source
- CertSoft Report Software
- Real Time System ORL

PART NUMBERS

- OMC-QUAD 850/1300/1310/1550nm (w/ PM & VFL)
- OMC-1315 1310/1550nm (w/ PM & VFL)
- OMC-8513 850/1300nm (w/ PM & VFL)
- OMC-PON 1310/1550nm, Live 1625nm (w PM & VFL)
- OMC-CWDM-CL 1551/1571/1591/1611nm (w/ PM & VFL)
- OMC-CWDM-S 1471/1491/1511/1531nm (w/ PM & VFL)

Advanced features in a small package:

The MINI-CAT OTDR is among the smallest full-featured color touchscreen OTDR's on the market. This unit includes all the features expected in today's hand held OTDR and more: bright color touch screen, project management, file storage, Fib-R-Map schematic event analysis, pass/fail threshold settings and onboard context-sensitive Express Help system to keep the learning curve as short as possible.

Easy-to-use:

The MINI-CAT OTDR is a user-friendly touch screen unit with a bright color display and screen rotation for portrait or landscape trace viewing. It operates in simple fault finder mode, construction or expert modes.

Powerful and customizable:

When equipped with the optional video scope, it is a powerful video inspection system with IEC61300-3-35 auto pass/fail capabilities. Additional optional features include a broadband power meter and visual fault locator. The MINI-CAT OTDR is available in SM or MM dual, Quad, PON and CWDM wavelength configurations.

Bluetooth compatible with Real-Time functionality:

The OTDR is operated/charged with a standard 5V USB charging system, or use the USB cable to connect the OTDR to a laptop for full real-time operation on Windows™. It can also be operated via Bluetooth with a compatible Android phone or tablet.

SPECIFICATIONS

Mini-Cat-OTDR Specifications	
Wavelength	850, 1300, 1310, 1550 and 1625 ± 20 nm (CWDM Wavelengths 1471-1611nm ± 3 nm)
Dynamic Range	26/27dB MM, 33/33dB SM, (1310/1550/1625 PON 37/38/385dB) (CWDM wavelengths 35dB)
Pulse Width	5 - 20,000 ns
Units of Measurement	km, ft, kf, mi
Event Dead zone	1m
Attenuation Dead Zone	4m
Resolution	.125 - 32m
Distance Uncertainty	$\pm(0.75m + 0.005\% \times \text{distance} + \text{sampling resolution})$
Full Scale Distance Range	0.25-64km MM, 0.25-260km SM
Typical Real-time Refresh Rate	2 Hz
Group Index of Refraction (GIR)	1.024 - 2.048
Linearity	$\pm .05$ dB/dB
Memory Capacity	~40,000
Memory Type	Internal
Power Supply / Charger	USB, 5V 1A
Battery	Li-ion 6hr typ.
Storage Temperature	-20 to 60 C
Operating Temperature Range	-10 to 50 C
Dimensions (w/out rubber boot)	6.25" L x 4.125" W x 1.875" H (159mm L x 105mm W x 48mm H)
Weight	1.5 lbs (0.7 kg)
Communications ports	USB and Bluetooth
Connector Styles	Choice of FC, ST, SC
Accessories Provided	Universal Power Adapter w/US, UK, Continental Europe, and Australian Plugs, Choice of FC/ST and SC Adapters, Android Application, Windows Compatible Software, Rubber Boot and Manual on CD

FIS reserves the right to change specifications without notice.

Light Source	
Fiber Type	Singlemode, Multimode
Wavelengths	850, 1300, 1310, 1490, 1550 and 1625 nm ± 20 nm
Output Power	0 dBm (-3 dBm @ 1625nm)
Laser Safety Classification	Class I Safety Per FDA/CDRH and IEC-825-1 Regulation
Modulation Modes	CW, 270 Hz, 1000 Hz, 2000 Hz

VFL (Option)	
Emitter Type	Laser
Wavelength	650nm ± 5 nm
Laser Safety Class	Class IIFDA21 CFR1040.10 & 1040.11 IEC 825-1: 1993
Connector Type	2.5mm Universal
Output Power	1mW Max.

Laser Safety

Class IIFDA21 CFR1040.10 & 1040.11 IEC 825-1: 1993

